

TECHNICAL DATA SHEET

ican Granit

Ican Granit is a fully matt, high quality paint for interior walls. It results in a velvety surface with no glossy appearance in raking light. This water based quality product can be used both as a primer and a topcoat, has high coverage and ensures a smooth result without brush marks. Because the painted surface is highly durable and washable it can withstand everyday wear and tear and the wall will stay beautiful for a long time.
EU limit value for this product (Cat A/a): 30g/l(2010). This product contains max. 30g/litre VOC.

Area of Use

Interior: Walls, ceilings

Substrates: Plasterboard, fabric, wallpaper and previously painted surfaces.

Application

The surface must be dry, dust-free and clean. Wash previously painted surfaces with facade cleaner and rinse with water. Glossy surfaces previously painted with acrylic must be sanded matt before painting. Apply with brush or suitable enamel-roller. After light diluting with water, it can also be applied by spraying. When applying tinted paint always try to apply complete areas with paint from the same can. Recommended 2 coats, depending on type and colour of surface to be painted. Apply under controlled conditions, where air, paint and surface temperature are not below +5°C. At high humidity drying time will be longer.

Technical Information

Sheen level: 3-5 (fully matt)

Coverage: 4-8m²/litre

Application: Brush, roller or spray (after dilution)

Recoating time: 3 hours (depending on air/surface temperature)

Shelf life: Max 2 yrs in dry, frost-free conditions

Solvent/Cleaning of tools: water

Resin: Styrene Acrylic with Ceramic Microspheres

Density: 1.3 kg/litre.

Washability: 15.000

Drying time: 1 hour dust dry (depending on air/surface temperature)

Safety

Handle with care. Consult material safety datasheet and follow all local and national regulations. Avoid inhalation and contact with skin and eyes. Do not swallow. Take precautions against possible risk of fire and explosion as well as protection of the environment. Apply only in well ventilated areas. Do not paint if the surface is colder than 7°C. Once opened, keep can tightly sealed.

Wipe away as much paint as possible from painting tools before cleaning with water. Liquid paint waste must not be poured down the drain, dispose of it according to local regulations. Hand in empty cans to your nearest recycling depot. **KEEP AWAY FROM CHILDREN.**

Environmental Protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.