

## TECHNICAL DATA SHEET

# icanMr. Bond

Mr. Bond is a solvent and softener-free impregnator agent for fixing powdery, absorbent and porous surfaces. With a very good surface penetration, alkali-resistance, fast drying and vapour-permeable qualities it promotes bonding and dries colourlessly, making it suitable for masonry, plasterwork, cement, concrete, wood and aerated autoclaved concrete. Can be added (at maximum 10%) to any water based paint to improve addition and bonding.

### Area of Use

Interior and exterior: Walls, ceilings, roof tiles, wooden and metal surfaces

Substrates: Masonry, plasterwork, cement, concrete and aerated autoclaved concrete (AAC) and for fixing powdery surfaces

### Application

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. Stirr well before use and apply with brush and paint roller. If necessary, dilute paint with max 5% of fresh water. Use only where application and drying can proceed above 10°C and relative humidity below 75%. Strong absorbing substances may have to be treated twice.

### Technical Information

Coverage: 2-6m<sup>2</sup>/litre

Colour: Transparent

Application: Brush or paint roller

Recoating time: After approx. 1h

Shelf life: Approx. 12 months in dry, cool, frost-free conditions

Solvent/Cleaning of tools: water

Resin: Acrylic dispersion

Density: 1.02 kg/litre.

Drying time: unavailable

### Safety

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

### Environmental Protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.