

TECHNICAL DATA SHEET

ican Priming Oil

Ican Priming Oil is a waterborne, deep-conditioning facade primer oil for new construction and repainting of exterior wood surfaces. Works as a primer in multiple-product systems and prevents cracking. The results is years of durable protection against moisture and unwanted growths.

EU limit value for this product (cat. A/f): 130g/l (2010). This product contains max 130 g/l VOC.

Area of Use

Exterior: Wooden surfaces

Application

The surface must be clean, dry and firm. Remove loose, porous and degraded wood with a steel brush. Wash previously-painted surfaces with a facade cleaner and disinfect mouldy surfaces.

Oil the dry timber using a brush or sponge. Properly treat end grain and timber joints. Wipe off the excess after a few minutes with a cloth or sponge.

Do not apply in temperatures below 8°C.

Technical Information

Sheen level: Depending on surface

Binder: Natural binding oils

Coverage: 6-10m²/litre

Application: Brush

Recoating time: 12 hours

Solvent/Cleaning of tools: water

Drying time: 6 hours (At 20°C and max 85% humidity)

Safety

May cause an allergic skin reaction. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

KEEP AWAY FROM CHILDREN.

Environmental Protection

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Dispose of contents/container in accordance with local regulations.

Contains 2-Octyl-2H-isothiazol-3-on, 3-iodo-2-propynylbutylcarbamate, 5-chloro-2-methyl-2H-isothiazol-3-one [EC no 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no 220-239-6] (3:1). EU