

TECHNICAL DATA SHEET

ican Woodstain

Ican Woodstain is a deep-conditioning alkyd-based woodstain for staining outdoor wooden surfaces. With its high vegetable oil content, the product lends the surface a deep lustre. Staining provides increased protection against UV radiation. Contains the biocidal substances DCOIT and OIT to protect the paint from fungal growth, EU limit value for this product (cat. A/e): 400g/l (2010). This product contains max 400g/l VOC.

Area of Use

Exterior: Wooden surfaces

Application

The surface must be clean, dry and firm. Use a steel brush to remove loose, porous and degraded wood. Wash previously-painted surfaces with a facade cleaner and disinfect mouldy surfaces. Apply 1-2 coats. Apply to the full length of the boards to achieve a uniform stain. The more layers you apply, the darker the colour. Do not paint during prolonged periods of cold or wet weather. Avoid painting hot or sunlit surfaces. Do not apply in temperatures below 8°C.

Technical Information

Sheen level: Depending on surface

Binder: Fat alkyd oils

Coverage: 4-7m²/litre

Application: Brush, roller or spray

Recoating time: 24 hours

Solvent/Cleaning of tools: water

Drying time: 16 hours (At 20°C and max 85% humidity)

Safety

Repeated exposure may cause skin dryness or crackling. Avoid breathing in vapours. May cause an allergic reaction.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

KEEP AWAY FROM CHILDREN.

Environmental Protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.

Contains Ethyl methyl ketoxime, 2-Octyl-2H-isothiazol-3-one, 4,5-Dichloro-2-octyl-2H-isothiazol-3-one.