

Golvolja Floor Oil

Eicó Golvolja Floor Oil is a solvent free, unique blend of renewable pure natural oils. It impregnates, nourishes and penetrates deep into the pores of the wood. It fills up the pores without shrinkage during drying. Second coat can be applied after 24 hours and can be polished. A surface treated with eicó Golvolja Floor Oil remains anti-static and breathing and preserves the matt look of oiled wood, while providing good resistance against water, dirt and stains.

AREA OF USE

Interior: Wood surfaces

Substrates: Wooden floors and other interior wooden surfaces.

APPLICATION

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. Apply with brush, paint roller air spray or airless spray. If necessary, dilute paint with max 5% of fresh water. Use only where application and drying can proceed above 5°C and relative humidity below 75%.

TECHNICAL INFORMATION

Sheen level: About 20 (at 60°)

Coverage: 10m²/litre per coat, corresponding to about 35-50µ average dry film thickness

Colour: White and in base A which can be tinted in a vast range of colours

Application: Brush, paint roller, air spray or airless spray

Viscosity: About 30 poise (25°C, Brookfield HA5/50)

Recoating time: Between 4 and 8 hours depending on drying conditions

Solvent/Cleaning of tools: water

Solid content: about 50% by weight or about 37% by volume (theoretical), varying slightly with colours

Density: 1.3 kg/litre at 25°C, varying slightly with colours

Drying time: About 1 hour at 20°C

SAFETY

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

ENVIRONMENTAL PROTECTION

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.