iCan Metallic

Data Sheet



Metallic is a solvent-free, satin-gloss metallic enamel. With a very good moisture-regulating quality it has low environmental impact, is elastic and easily cleaned. Metallic has good coverage, fluidity and excellent exterior durability.

Area of Use

Interior and exterior: Wooden surfaces

Application

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. Stir well before use and apply with brush and paint roller. If necessary, and lower gloss level is desired, dilute paint with max 5% of fresh water. Use only where application and drying can proceed above 10°C and relative humidity below 75%. Strong absorbing substances may have to be treated twice.

Technical Information

Coverage: around 8-10m2/litre (at $100\mu m$ wet film thickness)

Colour: 24 metallic colours from the Global Colour Matching System

Application: Brush, paint roller or airless sprayer

Recoating time: After approx. 12h (and 48h for best results) Shelf life: Approx.12 months in dry, cool, frost-free conditions

Solvent/Cleaning of tools: water Resin: Polyurethan/alkyd emulsion

Density: 1.06 kg/litre. Solids content: 40%

Drying time: 1 hour, dust free

Safety

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

Environmental Protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.



Tel: +44 (0)845 073 9432 Fax: +44 20 7384 3723 Email: info@eico.co.uk