

# iCan Mr Bond

## Data Sheet

---



Mr. Bond is a solvent and softener-free impregnator agent for fixing powdery and absorbent surfaces. With a very good surface penetration, alkali-resistance, fast drying and vapour-permeable qualities it promotes bonding and dries colourlessly, making it suitable for masonry, plasterwork, cement, concrete and aerated autoclaved concrete.

### Area of Use

**Interior and exterior:** Walls, ceilings, roof tiles, wooden and metal surfaces

**Substrates:** Masonry, plasterwork, cement, concrete and aerated autoclaved concrete (AAC) and for fixing powdery surfaces.

### Application

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. Stir well before use and apply with brush and paint roller. If necessary, dilute paint with max 5% of fresh water. Use only where application and drying can proceed above 10°C and relative humidity below 75%. Strong absorbing substances may have to be treated twice.

### Technical Information

**Coverage:** 2-6m<sup>2</sup>/litre

**Colour:** Transparent

**Application:** Brush or paint roller

**Recoating time:** After approx. 1h

**Shelf life:** Approx. 12 months in dry, cool, frost-free conditions Solvent/Cleaning of tools: water

**Resin:** Acrylic dispersion

**Density:** 1.02 kg/litre.

**Drying time:** unavailable

### Safety

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

---

**KEEP AWAY FROM CHILDREN**

---

### Environmental Protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.



eicó Paints Limited. 861-863, Fulham Road, London, SW6 5HP

Tel: +44 (0)845 073 9432 Fax: +44 20 7384 3723 Email: [info@eico.co.uk](mailto:info@eico.co.uk)