

# eicó Alterior Eggshell

## Data Sheet

---



eicó Alterior Eggshell is a high quality waterborne paint, made using only the finest raw materials. It dries to a non-yellowing, eggshell finish and has excellent colour retention. It has low dirt pick-up, good weathering properties and washability. eicó alterior eggshell adheres well to aged alkyd paints, is easy to use and has a very good hiding power. It is an environmentally friendly product with very little odour, is APEO and solvent free with a low VOC rating (VOC  $\leq$  2.5%). EU limit for this product (Cat A/i): 140g/ltr (2007)/140g/ltr (2010). This product contains max 30g/litre VOC measured at 250°C.

### AREA OF USE

**Interior:** Walls, ceilings, roof tiles.

**Substrates:** Concrete, masonry, cements, rendering plaster, plaster board, lining paper, glass fibre, woodwork and steel (primed), etc.

### APPLICATION

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. On rough surfaces it may be necessary to dilute the paint by about 10% with fresh water. Apply with brush, paint roller air spray or HVLP spray. Use only where application and drying can proceed at temperatures above 7°C, preferably above 10°C and relative humidity below 85%. Temperature of surface should be 7 to 35°C.

### TECHNICAL INFORMATION

**Gloss level:** 20 (eggshell)

**Coverage:** 8-10m<sup>2</sup>/litre

**Volume solid:** 40%

**Solvent/Cleaning of tools:** water

**Drying time:** 2-3 touch dry

**Recoating time:** Min. 6-8 hours (depending upon temperature and relative humidity)

### SAFETY

Handle with care. Consult Material Safety Data Sheets and follow all local or national regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosion, as well as protection of the environment. Apply only in well-ventilated areas.

Do not paint if the surface is colder than +7°C. Once opened, keep cans tightly sealed. Wipe away as much paint as possible from painting tools before cleaning with water. Liquid paint waste must not be poured down the drain – dispose it according to local regulations. Hand in empty cans to local authority for recycling.

---

KEEP AWAY FROM CHILDREN

---

### ENVIRONMENTAL PROTECTION

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.

# eicó

eicó Paints Limited. 861-863, Fulham Road, London, SW6 5HP

Tel: +44 (0)845 073 9432 Fax: +44 20 7384 3723 Email: [info@eico.co.uk](mailto:info@eico.co.uk)